


Original Claims 1-13 have been canceled and new Claims 14-30 are presented for examination. New Claims 14-30 are believed to be self-evident from the original disclosure, including original Claims 1-13, and thus are not deemed to raise any issues of new matter.

A new substitute Figure 7 is also submitted herewith which correctly labels element 144.

The present application is believed to be in condition for a full and thorough examination on the merits. An early and favorable consideration of the present application is hereby respectfully requested.

Respectfully submitted,

OBLON, SPIVAK, McCLELLAND,
MAIER & NEUSTADT, P.C.



Gregory J. Maier
Registration No. 25,599
Attorney of Record
Surinder Sachar
Registration No. 34,423



22850

(703) 413-3000
Fax #: (703) 413-2220
GJM:SNS/cct

I:\atty\SNS\206338US-pr.wpd

Marked-Up Copy Serial No: _____ Amendment Filed on: _____ _____

IN THE SPECIFICATION

Please amend the specification as follows:

Page 7, replace the paragraph beginning at line 19 through page 8, line 3, with the following paragraph:

--According to the cask of next invention, [in the cask of the above-mentioned invention,] the shape of either one of the inner surface of a cavity of a shell main body that has a neutron shielding unit at its outer periphery and shields the γ -rays or the outer surface of a basket that has latticed cells structured by a plurality of angular pipes having neutron absorbing property, is matched with the shape of the other, whereby each used nuclear fuel aggregate is accommodated in each cell of the basket inserted into the cavity.--

Page 11, replace the paragraph at lines 13-20 with the following paragraph:

--According to the cask of next invention, [in the cask of the above-mentioned invention,] spacers are provided between a cavity of a shell main body that has a neutron shielding unit at its outer periphery and shields the γ -rays and a basket that has latticed cells structured by a plurality of angular pipes halving neutron absorbing property, whereby each used nuclear fuel aggregate is accommodated in each cell of the basket inserted into the cavity.--

Page 30, replace the paragraph beginning at line 8 through page 31, line 6, with the following paragraph:

--As explained above, according to the cask 100 relating to the first embodiment of the present invention, the inside of the cavity 102 of the shell main body 101 is mechanically processed, and the angular pipes 132 that structure the outer periphery of the basket 130 are inserted into the cavity in a closely adhered state. Therefore, it is possible to improve the thermal conductivity of the heat from the angular pipes 132. Further, as the space area inside the cavity 102 can be eliminated, it is possible to make the shell main body 101 in compact and with reduced weight. Even in this case, the number of the angular pipes 132 that can be accommodated is not reduced. On the contrary, when the external diameter of the shell main body 101 is made the same as that of the cask shown in Fig. [16] 19, it becomes possible to secure the number of cells by that amount, and it is possible to increase the number of used nuclear fuel aggregates that can be accommodated. Specifically, the cask 100 can accommodate 69 used nuclear fuel aggregates, and it is also possible to restrict the external diameter of the cask main body 116 to 2,560 mm and its weight to 120 tons. When the above structure is employed, it has actually become possible to accommodate 69 used nuclear fuel aggregates after satisfying the required weight limit and the size limit of the cask.--

Page 32, replace the paragraph beginning at line 25 through page 33, line 9, with the following paragraph:

--Fig. 12 is a perspective view showing a cask relating to a second embodiment of the present invention. This cask 200 has a structure that spacers 201 for thermal conduction are further provided on the cask 500 shown in Fig. [16] 19. These spacers 201 fill space areas S, and efficiently conduct heat from angular pipes 510 to a shell main body 501. The material for the spacers 201 is carbon steel that is the same as the material for the shell main body 501. The spacers 201 are manufactured by casting or forging or by a mechanical processing according to the shapes of the space areas S.--

IN THE CLAIMS

Claims 1-13 (Canceled).

Claims 14-30 (New).